

BLOCK 1	
LOT NUMBER	MINIMUM TOP OF FOUNDATION ELEVATION (T.O.F.)
1	4525.53
2	4522.93
3	4523.42
4	4523.42
5	4523.42
6	4523.42
7	4522.93
8	4522.07
9	4517.35
10	4509.64
11	4508.27
12	4506.49
13	4505.49
14	4502.85
15	4500.00
16	4497.63
17	4495.74
18	4493.99
19	4492.08
20	4490.55
21	4489.57
22	4487.72
23	4485.32
24	4482.92
25	4480.53
26	4477.81
27	4476.19
28	4479.90

BLOCK 2	
LOT NUMBER	MINIMUM TOP OF FOUNDATION ELEVATION (T.O.F.)
1	4479.90
2	4476.65
3	4476.89
4	4476.89
5	4475.93
6	4474.46
7	4474.46
8	4475.40
9	4476.32
10	4477.12
11	4477.12

BLOCK 3	
LOT NUMBER	MINIMUM TOP OF FOUNDATION ELEVATION (T.O.F.)
1	4480.05
2	4483.66
3	4486.65
4	4486.65
5	4486.60
6	4485.69
7	4484.18
8	4483.27
9	4482.24
10	4482.24
11	4483.27
12	4483.72
13	4484.57
14	4485.42
15	4486.32
16	4488.31
17	4489.40
18	4489.97

BLOCK 4	
LOT NUMBER	MINIMUM TOP OF FOUNDATION ELEVATION (T.O.F.)
1	N/A
2	4515.16
3	4512.35
4	4509.77
5	4506.97
6	4504.56
7	4504.27
8	4508.74
9	4511.44
10	4514.02
11	4515.35
12	4515.35
13	4515.35
14	4514.02
15	4512.72
16	4510.05
17	4508.11
18	4506.57
19	4504.27
20	4500.36
21	4499.89
22	4499.54
23	4498.70
24	4497.79
25	4496.88
26	4496.07
27	4495.16
28	4494.25
29	4493.33
30	4492.53
31	4491.57
32	4489.97

BLOCK 5	
LOT NUMBER	MINIMUM TOP OF FOUNDATION ELEVATION (T.O.F.)
1	4509.64
2	4501.86
3	4498.96
4	4497.12
5	4495.39
6	4493.82
7	4494.79
8	4496.73
9	4497.49
10	4497.55
11	4497.55
12	4497.55
13	4497.26
14	4496.24
15	4493.61
16	4486.77
17	4484.36
18	4481.99
19	4479.58
20	4477.36
21	4476.08
22	4478.8
23	4486.01
24	4486.73
25	4487.98
26	4489.28
27	4490.63
28	4491.79
29	4492.84

BLOCK 5 CONTIUED	
LOT NUMBER	MINIMUM TOP OF FOUNDATION ELEVATION (T.O.F.)
30	4492.84
31	4492.84
32	4492.84
33	4491.79
34	4490.44
35	4488.95
36	4487.41
37	4486.33
38	4487.46
39	4490.42
40	4491.94
41	4492.80
42	4493.61
43	4494.53
44	4495.45
45	4496.30
46	4497.22
47	4498.12
48	4499.89
49	4500.95
50	4501.81
51	4502.62
52	4503.15
53	4503.38
54	4503.30
55	4506.44
56	4509.28
57	4513.28

NOTES:

1. GRADING SHALL BE SLOPED AT 3% AWAY FROM THE BUILDING FOR A MINIMUM OF 10'.
2. SIDE OF LOT SHALL BE GRADED SUCH THAT RUNOFF IS INTERCEPTED AND DIRECTED TO FRONT AND/OR REAR OF LOT.
3. MINIMUM TOP OF FOUNDATION ELEVATIONS SHOWN ARE CALCULATED BY ADDING 18" TO THE HIGHEST BACK OF CURB ADJACENT TO THE LOT, AS REQUIRED BY THE CITY OF GILLETTE.
4. FINISH FLOOR ELEVATION MAY VARY ONLY IF GRADING AND DRAINAGE ARE APPROVED BY THE CITY OF GILLETTE.

Prepared for:
MORNINGSIDE, LLC
 4506 WIGWAM BLVD
 GILLETTE, WYOMING 82717
 (307) 687-0600

4506 Wigwam Blvd.
 P.O. Box 2185
 Gillette, Wyoming 82718
 307-687-0600
PCA ENGINEERING, INC.

Copyright © All Rights Reserved by PCA Engineering, Inc.
 Drawn by: REW Design by: REW Reviewed by: JLT
 Revision Date Revision Description
 08/2008 D.O.C.R.

PCA Project Number: 063131.00
 Plot Date: Aug 15, 2008 -- 8:11am
 G:\PROJECTS\06313100\ABDWgs\Utilities\OVERALL UTILITIES 2.dwg
 Layout: Foundation Elevations
 X-Ref: ...

MORNINGSIDE ESTATES

DRAWINGS OF CONSTRUCTION RECORD

FOUNDATION ELEVATIONS

SHEET 10 OF 125